



# INDUSTRIAL THREADED PRODUCTS INC.

13580 FIRESTONE BLVD. , SANTA FE SPRINGS, CA 90670

800-976-BOLT FX: 800 646 4249

www.itpbolt.com

# 55% NEOPRENE<sup>®</sup> RUBBER GASKET PLAIN RUBBER OR SOLID RUBBER

## SUBMITTAL SPECIFICATIONS

GASKETS MEET THE PRESSURE RATINGS, DRILLING AND  
DIMENSIONS OF ANSI / ASME B16.21

### TECHNICAL DATA

MANUFACTURES	STYLE	COLOR	BINDER	TEMP MAX	HARDNESS SHORE A	TENSILE STRENGTH ASTM F-152
AMERICAN BILTRITE	AB263	BLACK	CR/SBR	-20 TO190°	60	1000

### COMMERCIAL GRADE

### AVAILABILITY

FULL FACE     RING     1/16"     1/8"     1/4"     3/16"

**SERVICE:** Neoprene Sheet is specifically compounded to provide moderate resistance to oils and gasoline in such applications as gaskets an flanges in gas permeable situations. Suited for Hot Water, Cold Water, and Wastewater.

**GENERAL DESCRIPTION:** A Tough CR Compound, Adaptable to extreme weather conditions since it resists Rotting, Checking and Cracking due to Ozone Exposure.

\* NEOPRENE IS A REGISTERED TRADEMARK OF DuPONT