

Industrial Threaded Products, Inc.

Corporate Headquarters

515 North Puente Street, Brea, CA 92821
(562) 802-4626 (714) 521-5902 Fax (562) 802-4641

112027 Arrow Route
Rancho Cucamonga,
CA 91739
(909) 466-9445
Fax (909) 945-2696

1832 G Street
Fresno, CA 93706
1 (800) 976-BOLT
Fax 1 (800) 646-4249

2145 S. 11th Avenue. #130
Phoenix, AZ 85007
1 (800) 976-BOLT
Fax 1 (800) 646-4249

CLOTH INSERTED RUBBER GASKET

SUBMITTAL SPECIFICATIONS

GASKETS MEET THE PRESSURE RATINGS, AND DRILLING
DIMENSIONS OF ANSI / ASME B16.2.1
ASTM D-2000 1AA805

TECHNICAL DATA

MANUFACTURES	STYLE	COLOR	BINDER	TEMP MAX	HARDNESS SHORE A	TENSILE STRENGTH ASTM F-152
AMERICAN BILTRITE	2102	BLACK	SBR	180	60	700
ELONGATION	FABRIC TYPE 2.0 OZ		NUMBER OF PLYS PER THICKNESS		FINISH MATERIAL AVAILABLE	
250	POLY FABRIC		2 PLY		THRU 1/8" CLOTH	

MULLEN BURST TEST= 300 PSI AVERAGE PER PLY

COMMERCIAL GRADE

AVAILABILTY

FULL FACE

RING

1/8"

1/16"

SERVICE: Recommended for service in cold and hot water, air, saturated steam, low pressure steam or hydraulic services. Suited for all types of gauges, meters and valves where pressure areas are subject to movement.

GENERAL DESCRIPTIONS: A tough SBR compound and close weave poly fabric construction to resist tearing. Provides both flexibility and uniform structural strength for flange sealing. One ply of fabric per 1/16 inch thickness.