



Industrial Threaded Products, Inc.

Corporate Headquarters

13580 Firestone Blvd., Santa Fe Springs, CA 90670
(562) 802-4626 (714) 521-5902 Fax (562) 802-4641

112027 Arrow Route
Rancho Cucamonga,
CA 91739
(909) 466-9445
Fax (909) 945-2696

16701 Stagg Street, "A"
Van Nuys, CA 91406
(818) 786-0916
Fax (818) 786-1620

6474 Patterson Pass Rd. A
Livermore, CA 94545
(800) 566-8831
Fax (800) 646-4249

1832 G Street
Fresno, CA 93706
1 (800) 976-BOLT
Fax 1 (800) 646-4249

2145 S. 11th Avenue. #130
Phoenix, AZ 85007
1 (800) 976-BOLT
Fax 1 (800) 646-4249

DOMESTIC PREMIUM RED RUBBER GASKET GRADE 1

SUBMITTAL SPECIFICATIONS
GASKETS MEET THE PRESSURE RATINGS, AND DRILLING
DIMENSIONS OF ANSI / ASME B16.2.1

TECHNICAL DATA

MANUFACTURES	STYLE	COLOR	BINDER	TEMP MAX	HARDNESS SHORE A	TENSILE STRENGTH ASTM F-152
GARLOCK BAYSTATES	22	RED	SBR	180	65	1000

COMMERCIAL GRADE

AVAILABILITY

FULL FACE

RING

1/8"

1/16"

SERVICE: Recommended for service in cold and hot water, air, steam and some weak acids. Gasket should not be used in strong acids, oils, grease and chlorates. It offers little resistance to ozone and the majority of hydro carbonates. This gasket is not recommended for wastewater or sludge.

GENERAL DESCRIPTIONS: An economical, non oil resistant compound that resists flow under compression. Offers moderate to good performance against aging and low pressure. Gasket is abrasion, tear resistant and easily conforms to uneven flange surfaces.