



Industrial Threaded Products, Inc.

Corporate Headquarters

13580 Firestone Blvd., Santa Fe Springs, CA 90670
(562) 802-4626 (714) 521-5902 Fax (562) 802-4641

112027 Arrow Route
Rancho Cucamonga,
CA 91739
(909) 466-9445
Fax (909) 945-2696

16701 Stagg Street, "A"
Van Nuys, CA 91406
(818) 786-0916
Fax (818) 786-1620

6474 Patterson Pass Rd. A
Livermore, CA 94545
(800) 566-8831
Fax (800) 646-4249

1832 G Street
Fresno, CA 93706
1 (800) 976-BOLT
Fax 1 (800) 646-4249

2145 S. 11th Avenue. #130
Phoenix, AZ 85007
1 (800) 976-BOLT
Fax 1 (800) 646-4249

GARLOCK 98206 EPDM GASKET SULFUR CURED

SUBMITTAL SPECIFICATIONS

GASKETS MEET THE PRESSURE RATINGS, DRILLING AND DIMENSIONS OF ANSI / ASME
B16.2.1

TECHNICAL DATA

MANUFACTURES	STYLE	COLOR	BINDER	TEMP MAX	HARDNESS SHORE A	TENSILE STRENGTH ASTM F-152
GARLOCK	98206	BLACK	EPDM	275	85	1500

COMMERCIAL GRADE

AVAILABILITY

 FULL FACE RING 1/8" 1/4"

SERVICE : Excellent for applications which involve extreme temperature and or weather conditions. It is used extensively in high temperature installations. It offers ozone and chemical resistance as well as resistance to high temperatures.

GENERAL DESCRIPTIONS: Also provides excellent resistance to animal and vegetable oils, water, steam, and oxygenated solvents. Meets and or exceeds ASTM D2000 and is NSF 61 Approved