

# NEOPRENE® RUBBER GASKET PLAIN RUBBER OR SOLID RUBBER

## SUBMITTAL SPECIFICATIONS

GASKETS MEETS THE PRESSURE RATINGS, DRILLING AND DIMENSIONS OF ANSI/ASME B16.21 and AWWA C111

## TECHNICAL DATA

MANUFACTURES	STYLE	COLOR	BINDER	TEMP MAX	HARDNESS SHORE A	TENSILE STRENGTH ASTM F-152
AMERICAN BILTRITE	AB262	BLACK	CR	170°	60	700

## COMMERCIAL GRADE

## AVAILABILITY

<input type="checkbox"/> Full Face	<input type="checkbox"/> Ring	<input type="checkbox"/> 1/16"	<input type="checkbox"/> 1/8"	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/16"
------------------------------------	-------------------------------	--------------------------------	-------------------------------	-------------------------------	--------------------------------

GENERAL DESCRIPTION: A tough CR compound adaptable to extreme weather conditions since it resists rotting, checking, and cracking due to ozone exposure.

- NEOPRENE IS A REGISTERED TRADE MARK OF DuPONT

\*\*Domestically manufactured in the USA\*\*