



Industrial Threaded Products, Inc.

Corporate Headquarters

13580 Firestone Blvd., Santa Fe Springs, CA 90670
(562) 802-4626 (714) 521-5902 Fax (562) 802-4641

112027 Arrow Route
Rancho Cucamonga,
CA 91739
(909) 466-9445
Fax (909) 945-2696

16701 Stagg Street, "A"
Van Nuys, CA 91406
(818) 786-0916
Fax (818) 786-1620

6474 Patterson Pass Rd. A
Livermore, CA 94545
(800) 566-8831
Fax (800) 646-4249

1832 G Street
Fresno, CA 93706
1 (800) 976-BOLT
Fax 1 (800) 646-4249

2145 S. 11th Avenue. #130
Phoenix, AZ 85007
1 (800) 976-BOLT
Fax 1 (800) 646-4249

HEX BOLTS & MJ T-BOLTS T-304 STAINLESS STEEL

SUBMITTAL SPECIFICATIONS

Abstract of ASTM F593 & F-594

GRADE: UNSTABILIZED 18 CHROMIUM, 8 NICKEL (ANSI TYPE 304)

CHEMICAL REQUIREMENTS

Chemical analysis shall be performed in accordance with ASTM A751

CARBON MAX	MANGANESE MAX	PHOSPHOROUS MAX	SULFUR MAX	SILICON MAX	CHROMIUM	NICKEL	COPPER
0.08	2.00	0.045	0.030	1.00	18.0 To 20.0	8.0 To 10.5	1.00

MECHANICAL REQUIREMENTS

HARDNESS ROCKWELL	TENSILE STRENGTH	YIELD STRENGTH	ELONGATION
MIN B80-C32	(KSI) MIN 85	(KSI) MIN 45	25

HEX NUTS ASTM A593 (ASME B18.2.2)

HEAVY HEX NUTS ASTM A594 (ASME B18.2.2)

WASHERS T 304 STAINLESS STEEL

Dimensional Data: Unless otherwise specified in the purchase order, parts shall be coarse threaded series as specified in the latest issue of ANSI/ASME B18.2.1, page C-1 or Hex Cap Screws (Finished Hex Bolts). Additional information can be found in ASTM F-593, DTD 1998/ (Stainless Steel Bolts, Hex Cap Screws) and in ASTM F-594, DTD 1998 (Stainless Steel Nuts).