



STANDARD FLAT WASHERS - 18-8 STAINLESS STEEL						
Size	OD		ID		TH	
	Outside Diameter		Inside Diameter		Thickness	
	Max	Min	Max	Min	Max	Min
4	.317	.307	.130	.120	.034	.028
6	.375	.370	.161	.151	.034	.028
8	.375	.370	.177	.167	.034	.028
10	.438	.432	.208	.198	.034	.028
1/4	.625	.620	.286	.276	.054	.046
5/16	.750	.745	.349	.339	.054	.046
3/8	.875	.870	.396	.386	.054	.046
3/8	1.000	.995	.396	.386	.066	.058
7/16	1.125	1.120	.505	.495	.066	.058
1/2	1.250	1.245	.567	.557	.066	.058
5/8	1.500	1.495	.693	.683	.084	.074
3/4	1.750	1.745	.817	.807	.097	.082
7/8	2.000	1.995	.943	.933	.117	.102
1	2.000	1.995	1.067	1.057	.133	.117

Description	A thin, flat, circular stamping with a centrally located hole, made from an 18-8 austenitic stainless steel.
Applications/ Advantages	Designed for use with 18-8 stainless steel screws and nuts in general industrial applications where parts are subject to corrosion.
Material	18-8 stainless steel