

Phone: (800) 976-BOLT Web: itpbolt.com Email: sales@itpbolt.com Email: purchasing@itpbolt.com BREA FRESNO RANCHO CUCAMONGA UNION CITY

## ALL THREADED ROD

SUBMITTAL SPECIFICATIONS Abstract of ASTM A307 Grade A

CHEMICAL REQUIREMENTS Chemical analysis shall be performed in accordance with ASTM A751

| CARBON | MANGANESE | PHOPHOROUS | SULFER |  |  |
|--------|-----------|------------|--------|--|--|
| MAX    | MAX       | MAX        | MAX    |  |  |
| 0.29   | 1.20      | 0.04       | 0.15   |  |  |

## MECHANICAL REQUIREMENTS

|                                | HARDNESS<br>BRINEL                   |          | HARDNESS<br>ROCKWELL |           | TENSILE<br>STRENGTH<br>(KSI) |            | ELONG/<br>IN 2 IN (5 |          |       |  |  |  |
|--------------------------------|--------------------------------------|----------|----------------------|-----------|------------------------------|------------|----------------------|----------|-------|--|--|--|
|                                | MIN                                  | MAX      | MIN                  | MAX       | MIN                          | MAX        | IIM                  | N        |       |  |  |  |
|                                | 121                                  | 241      | 69                   | 100       | 60                           | -          | 18                   | }        |       |  |  |  |
|                                |                                      |          |                      |           |                              |            |                      |          |       |  |  |  |
|                                | Hex Nuts                             | ASTM A56 | 3 (ASME E            | 318.2.2)  | Heavy                        | Hex Nuts A | STM A563 (A          | ASME B18 | .2.2) |  |  |  |
|                                |                                      |          |                      |           |                              |            |                      |          |       |  |  |  |
|                                | Washers ASTM F844-04 (ASME B18.22.1) |          |                      |           |                              |            |                      |          |       |  |  |  |
|                                |                                      |          |                      |           |                              |            |                      |          |       |  |  |  |
| ALL THREAD ROD MAY BE SUPPLIED |                                      |          |                      |           |                              |            |                      |          |       |  |  |  |
|                                |                                      | Pla      | in 🗌                 | Zinc F    | Plated                       | Hot Dip    | Galvanized           |          |       |  |  |  |
|                                |                                      |          |                      |           |                              |            |                      |          |       |  |  |  |
|                                | LOCATION                             |          |                      |           |                              |            |                      |          |       |  |  |  |
| Buried                         |                                      | Submerge | d 🗌                  | Above Gra | de                           | Below      | Grade                | Ot       | ther  |  |  |  |
|                                |                                      |          |                      |           |                              |            |                      |          |       |  |  |  |

ADDITIONAL INFORMATION: Additional information can be found in ASTM A307-07B, ASTM A563-04A