


Slotted





Phillips

FILLISTER HEADS FOR MACHINE SCREWS

ANSI B18.6.3

Nominal Size	A		H				O		J		T		M		G	N	Phillips Driver Size			
	Head Diameter		Height of Head				Width of Slot		Depth of Slot		Dimensions of Recess			Diameter	Depth	Width				
			Side Height		Total Height								Max					Min	Max	Min
	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min								
0	.096	.083	.043	.038	.055	.047	.023	.016	.025	.015	.067	.054	.039	.013	0					
2	.140	.124	.062	.053	.083	.066	.031	.023	.037	.025	.104	.091	.059	.017	1					
3	.161	.145	.070	.061	.095	.077	.035	.027	.043	.030	.112	.099	.068	.019	1					
4	.183	.166	.079	.069	.107	.088	.039	.031	.048	.035	.122	.109	.078	.019	1					
5	.205	.187	.088	.078	.120	.100	.043	.035	.054	.040	.143	.130	.067	.027	2					
6	.226	.208	.096	.086	.132	.111	.048	.039	.060	.045	.166	.153	.091	.028	2					
8	.270	.250	.113	.102	.156	.133	.054	.045	.071	.054	.182	.169	.108	.030	2					
10	.313	.292	.130	.118	.180	.156	.060	.050	.083	.064	.199	.186	.124	.031	2					
12	.357	.334	.148	.134	.205	.178	.067	.056	.094	.074	.259	.246	.141	.034	3					
1/4	.414	.389	.170	.155	.237	.207	.075	.064	.109	.087	.281	.268	.161	.036	3					
5/16	.518	.490	.211	.194	.295	.262	.084	.072	.137	.110	.322	.309	.203	.042	3					
3/8	.622	.590	.253	.233	.355	.315	.094	.081	.164	.133	.389	.376	.233	.065	4					



TORX® DRIVE PAN HEADS

Camcar

Screw Size	D		H		R	G	Driver Size	
	Head Dimensions				Recess Dimensions			
	Head Diameter		Head Height		Diameter (Ref)	Gauge Penetration (Min)		(Fallaway) Max Penetration
	Max	Min	Max	Min				
2	.167	.155	.062	.053	.094	.030	.022	T8
4	.219	.205	.080	.070	.111	.035	.026	T10
6	.270	.256	.097	.087	.132	.045	.031	T15
8	.322	.306	.115	.105	.155	.055	.036	T20
10	.373	.357	.133	.122	.178	.070	.040	T25
1/4	.492	.473	.175	.162	.221	.085	.044	T30
5/16	.615	.594	.218	.203	.266	.105	.047	T40