

# NEOPRENE® RUBBER GASKET SOLID RUBBER

## SUBMITTAL SPECIFICATIONS

GASKETS MEETS THE PRESSURE RATINGS, DRILLING AND DIMENSIONS OF ANSI/ASME B16.21 AND AWWA C111

## TECHNICAL DATA

MANUFACTURER	STYLE	COLOR	BINDER	TEMP MAX	HARDNESS SHORE A	TENSILE STRENGTH ASTM D412
GCP/PREMLENE	NES-XT	BLACK	CR	190	60 +/-5	MIN/TYPICAL 500/667

## COMMERCIAL GRADE

## AVAILABILITY

<input type="checkbox"/> Full Face	<input type="checkbox"/> Ring	<input type="checkbox"/> 1/16"	<input type="checkbox"/> 1/8"	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/16"
------------------------------------	-------------------------------	--------------------------------	-------------------------------	-------------------------------	--------------------------------

GENERAL DESCRIPTION: A tough CR compound adaptable to extreme weather conditions since it resists rotting, checking, and cracking due to ozone exposure.

NEOPRENE IS A REGISTERED TRADE MARK OF DuPONT

\*\*Domestically manufactured in the USA\*\*